

PGG 8/3

Powerful PGG 8/3 synchronous generator with constant 7 kW output, 4-stroke petrol engine and 25 l tank. For independent power supply with AC and three-phase current.



V
Stage V



Order no.

1.042-209.0

- Foldable push handle and puncture-proof tyres with robust cage frame
- Convenient electric start function with key switch, three-phase current (400 V)

Technical data

EAN code		4054278547947
Number of current phases	Ph	3
Voltage	V	400
Sound pressure level	dB(A)	76
Nominal power	kW	2
Rated performance (three-phase current)	kW	7
Power	kW	2.5
Performance (three-phase current)	kW	max. 7.5
Drive type		Petrol
Displacement	cm ³	440
Motor rating	kW / hp	9 / 12.2
Fuel consumption	l/h	4.5
Tank capacity	l	25
Runtime at 50% output	h	7
Runtime at 100% output	h	5.5
Weight incl. packaging	kg	99.6
Weight without accessories	kg	89.7
Dimensions (L × W × H)	mm	743 × 713 × 670

Equipment

Operating state display	■
DC output (12 V)	■
Protection class IP 23	■
Low oil and overload protection	■
Fuel gauge	■
Single phase socket type F (Schuko)	■
Three-phase socket CEE (16 A)	■
Automatic Voltage Regulation (AVR)	■

■ included in the scope of supply.



Extraordinary ease of use

- High mobility thanks to the foldable push handle and puncture-proof wheels.
- Electro start function for the convenient and quick start of the petrol engine.



Ultimate reliability and safety

- With overload and oil shortage protection as well as tubular steel frame for maximum safety.
- With automatic voltage regulator (AVR) for the operation of sensitive electronic devices.



Operation of Kärcher high-pressure cleaners

- Enables the use of high-pressure cleaners in areas without external power supply.
- Suitable for selected three-phase high-pressure cleaners.